

















Series 系列	Product Appearance 产品外观	Size(mm) 尺寸(mm)	Fast/Slow 快/慢断	Material 主要材质	Specification 规格范围	Voltage level 电压等级	Interrupting Rating 分断能力
S0402-F		0.95*0.5*0.28	快断	陶瓷	1.0A~5.0A	32V DC	35A@32V DC
S0603-F		1.6*0.8*0.4	快断	陶瓷	0.5A~6.0A	32V DC	0.5A~3.5A:50A@32V DC 4.0A~6.0A:35A@32V DC
S0603-S		1.6*0.8*0.4	慢断	陶瓷	0.5A~8.0A	32V DC	0.5A~3.5A:50A@32V DC 4.0A~6.0A:35A@32V DC 7.0A~8.0A:50A@32V DC
S0603-SD		1.6*0.8*0.4	慢断	陶瓷	1.0A~6.0A	63V DC	50A@63V DC
S1206-F		3.1*1.55*0.55	快断	陶瓷	0.5A~7.0A	32V DC	0.5A~3.5A:50A@32V DC 4.0A~7.0A:35A@32V DC
S1206-S		3.1*1.55*0.55	慢断	陶瓷	0.5A~7.0A	32V DC	0.5A~3.5A:50A@32V DC 4.0A~7.0A:35A@32V DC
S1206-FA		3.1*1.55*0.55	快断	陶瓷	8.0A~15.0A	32V DC	150A@32V DC
		3.1*1.6*0.8	快断	陶瓷	20.0A~30.0A	48V DC	300A@32V DC 200A@48V DC
S1206-FC		3.1*1.6*0.8	快断 AEC-Q200	陶瓷	1.0A~5.0A	100V DC	1.0A~5.0A:50A@100V DC
S1206-SD		3.1*1.55*0.55	慢断	陶瓷	0.5A~7.0A	63V DC	50A/63V DC 50A/63V AC
S6125-F		6.1*2.5*2.5	快断	瓷管	1-30A	1A-10A: AC125V/DC160V 12A-20A: 65V AC/65V DC 30A:72V DC	1A-10A: 50A 125V AC 50A 160V DC 100A 100V AC 12A-20A: 50A 65V AC 50A 65V DC 30A:150A 72V DC 500A 65V DC
S6125-H		6.1*2.5*2.5	高抗浪涌	瓷管	0.5A-5.0A	125V AC/DC	50A 125V AC 50A 125V DC
S6125-H2		6.1*2.5*2.5	高抗浪涌	瓷管	0.5A-5.0A	250V AC/125V DC	0.5A: 35A 250V AC 50A 125V DC 1A-5A: 50A 250V AC 50A 125V DC
S6125-M2		6.1*2.5*2.5	抗浪涌	瓷管	0.5A-5.0A	250V AC/125V DC	0.5A: 35A 250V AC 50A 125V DC 1A-5A: 50A 250V AC 50A 125V DC
S1032-F		10.25*3.2*3.2	快断	瓷管	20-60A	20A-30A:100V DC/ 72V DC/32V DC 40A-60A: 72V DC/60V DC	20A-30A:100V DC 300A 72VDC 500A/32V DC 1000A 40A-60A:72V DC 180A 60V DC 600A
S1245-S		12.1*4.5*4.5	慢断	瓷管	60A	60A: 84V DC	60A: 1000A 84V DC